



American National Rubber

PO Box 877 ** Ceredo, West Virginia 25507 ** Telephone: 1-844-267-2867 ** Fax: 304-453-6908

DATA SHEET

NEOPRENE

4219-NEU

Color:

Black

Specifications:

ASTM D-1056-00
ASTM D-1056-67(1)
SAE J18-02
GM 6086M(3)
GMN11106(3)
TSM1501G

2C2
SCE42
2C2
II
II
2C2

25% Compression Deflection (PSI)

5 - 9

Shore 00 Durometer (Approximate)

40 - 60

Density (Approximate p.c.f.)

8 - 14

Water Absorption By Weight

5%

Temperature Range

-70 to 200F

Weather Resistance:

UV
Ozone

Excellent
Fair

Accelerated Linear Shrinkage (Typical)

5%

Fuel B Resistance %

250

Tensile Strength (Typical)

70 PSI

Elongation (Typical)

130%

Flammability:

FM VSS No. 302
ASTM D 6576

Pass
Pass

UL Recognized Component Gasket Materials:
(Call Customer Service for Details)

File No. JMST 2

(1)Obsolete specification listed for reference only. ANR certifies to most recent revision of ASTM D-1056 and SAE J18.

(3)Certain sections of this specification will not apply to all products. Contact Customer Service for details.

American National Rubber disclaims responsibility for results of use of this information, which is furnished without charge, or of any product mentioned herein. It is the user's responsibility to make and be guided by his own testing before making a final decision on the type of material to be used in any application.

10/2014